

R-14S



90x90 TRACTRIX HORN

Our exclusive Tractrix® Horn technology and aluminum tweeters deliver the most impressive high-end response and greater extension, enhanced imaging and powerful dynamics. This creates the cleanest, most natural sound possible.

LINEAR TRAVEL SUSPENSION (LTS) TWEETER

A Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS Tweeters have been a hallmark of previous Reference lines, as well as our flagship Klipsch Palladium series, making it a core component of some of the best speakers in the world.

SPUN COPPER IMG WOOFER

Injection Molded Graphite (IMG) woofer is exceptionally light while being extremely rigid - providing remarkable low frequency response, with minimal cone breakup and distortion. When paired with the Tractrix Horn-loaded LTS tweeter, it provides speaker efficiency highest in its class.

WDST (WIDE DISPERSION SURROUND TECHNOLOGY)

Provides maximum surround coverage and placement flexibility

MDF CABINET WITH BRUSHED POLYMER VENEER FINISH

Contemporary aesthetic with absolute durability that results in a seamless integration into any décor.

5-WAY BINDING POSTS

Sturdy, versatile and high quality terminals that provide maximum connection flexibility.

KEYHOLE MOUNT

Allows the speaker to be wall-mounted with ease.

SPECIFICATIONS

FREQUENCY RESPONSE	83Hz - 24kHz +/- 3dB
SENSITIVITY	89dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	50W/200W
NOMINAL IMPEDANCE	8 Ohms Compatible
LOW FREQUENCY EXTENSION	78Hz
CROSSOVER FREQUENCY	2200Hz
HIGH FREQUENCY DRIVER	Dual 1" (2.54cm) Aluminum diaphragm compression drivers mated to 90° x 90° square Tractrix® Horn
LOW FREQUENCY DRIVER	4" (10.2cm), copper spun IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Sealed (WDST)
INPUTS	Single binding posts
HEIGHT	6.66" (16.9 cm)
WIDTH	15" (38.1 cm)
DEPTH	6.5" (16.5 cm)
WEIGHT	8lbs (3.6 kg)
FINISH	Brushed Black Polymer Veneer
BUILT FROM	2014